

ALUMINUM

Project Fact Sheet



MICROSMOOTH® PROCESS ON ALUMINUM WHEELS

NEW PROCESS USING MICROSMOOTH SUBSTANTIALLY REDUCES ENERGY, CHEMICAL USAGE, AND WASTE FOR ALUMINUM TREATED WITH NICKEL/CHROME PLATING

Benefits

- Reduces electric energy use by 33% and natural gas requirements by 59%
- Potential to save an estimated 350 billion Btu by 2010
- Cuts water usage and treatment by 50%
- Lowers production costs by 30% to 40% per wheel
- Eliminates the use of zincate in conventional plating, reducing worker health risks
- Reduces greenhouse gas emissions by 46%
- Based on projected nationwide production of 12.4 million wheels by 2010, the new technology has the potential to:
 - Save 173,000 tons of waste per year (formerly used in zincate processing)
 - Eliminate 6.5 tons per year in the caustic etch step
 - Reduce copper consumption by 51 tons per year

Applications

While this project focuses on aluminum wheel manufacturing for the automotive industry, the plating process can also be applied to computer disk manufacturing.

Project Partners

NICE³ Program
Washington, DC

New York State Energy and
Research Development Authority
Albany, NY

Metal Arts Company, Inc.
Rochester, NY

Metal Arts Company, Inc., in conjunction with the NICE³ program, is developing for full-scale demonstration and commercialization an innovative electroless nickel-plating process for the aluminum industry that reduces electrical energy use by one-third and natural gas usage by 59%. Microsmooth eliminates wastes associated with zincate use, as well as worker exposure to zincate-related chemicals (including cyanide), while increasing the product quality of aluminum chrome plating for finished products. This method does not require electric plating, but depends on Microsmooth and specially prepared aluminum surfaces to produce a smoother, more durable product than is currently available. By removing zincate from the manufacturing process, nitric acid and other liquid wastes generated by current technology are eliminated. There is also a substantial reduction in greenhouse gas emissions.

MICROSMOOTH PROCESS ON ALUMINUM WHEELS



The Microsmooth bathing process improves aluminum-chromium plating quality, while substantially reducing electric and natural gas usage in the plating process.



Project Description


Goal: The project goals are to demonstrate a fully operational, limited commercial production-scale unit (approximately 1/20 the cost and size of a full production line) for applying Microsmooth and to provide necessary data for full-scale implementation in industry-wide application. The unit will continue to serve in limited use as a test unit toward developing the best processing methods and chemistries possible.

Prior to receiving a NICE³ grant for this project, Metal Arts conducted tests over a 3-year period to determine proper activator bath formulas, mixing requirements, adhesion characteristics, and energy usage for the process. When Microsmooth is applied to aluminum automotive wheels, forged aluminum is used with a substrate surface that produces fewer pores and less surface blistering. Wheels that are processed with Microsmooth go through a simplified plating method that increases energy efficiency and eliminates zincate use, while improving corrosion resistance.

Metal Arts Company, Inc., is demonstrating this new technology with assistance from the New York State Energy and Research Development Authority and the NICE³ Program in the Department of Energy's Office of Industrial Technologies.

Progress and Milestones

- Optimize chemistry by using coupon-sized aluminum pieces.
- Monitor, evaluate, and refine activator baths, mixing requirements, plating characteristics, energy and raw material requirements, and processes.
- Determine plating thickness and corrosion resistance through test protocols and evaluation criteria.
- Conduct testing on larger pieces, including complete wheels, to determine plating thickness, corrosion resistance, electrochemical potential, and porosity.
- Develop a statistical process control system to quantify and standardize mixing regimens and to catalog plating characteristics, including: adhesion, corrosion characteristics, metal turnovers, bath-loading factors, and run-to-run consistency.
- Demonstrate a fully operational, limited production-scale process.
- Implement the successful Microsmooth process at Alcoa.



NICE³ – National Industrial Competitiveness through Energy, Environment, and Economics: An innovative, cost-sharing program to promote energy efficiency, clean production, and economic competitiveness in industry. This grant program provides funding to state and industry partnerships for projects that demonstrate advances in energy efficiency and clean production technologies. Awardees receive a one-time grant of up to \$525,000. Grants fund up to 50% of total project cost for up to 3 years.

For project information, contact:

Stanley J. Dahle
Metal Arts Company, Inc.
800 St. Paul Street
Rochester, NY 14605
Phone: (716) 546-7170
Fax: (716) 546-7202

For more information about the NICE³ Program, contact:

Lisa Barnett
Program Manager
NICE³ Program
Phone: (202) 586-2212
Fax: (202) 586-7114
lisa.barnett@ee.doe.gov

Visit our home page at
www.oit.doe.gov

Office of Industrial Technologies
Energy Efficiency and
Renewable Energy
U.S. Department of Energy
1000 Independence Avenue SW
Washington, D.C. 20585-0121



Order # NICE³ AL-1
February 2002